ALPHA 3477UOR200P63

EAN 4031582306194

Swivel castor with total lock, tail end of castor, housing made of pressed steel, bright zinc plated, blue passivated, double ball bearing swivel head, wheel axle with nut, dustguard, plate fitting. Wheel centre made of Polyamide, roller bearing





Picture may differ from original product


Technical Data

| Wheel diameter | 200 mm |
|------------------------|----------------|
| Width of Tread | 50 mm |
| Castor width | 96 mm |
| Size of Plate | 137 x 105 mm |
| Plate hole centres | 105 x 80/75 mm |
| Plate hole | 11 mm |
| Dome-Ø | 96 mm |
| Offset | 55 mm |
| Swivel Interference | 334 mm |
| Overall height | 240 mm |
| Temperature | - 25 / + 80 °C |
| Standard | EN 12532 |
| Weight | 2.726 kg |
| Swivel Radius | 167 mm |
| Hardness of tread | Shore D 75 |
| Load capacity | 350 kg |
| Load capacity (static) | 700 kg |


Advantages at a glance

| Roll performance | • • • 0 0 |
|----------------------|-----------|
| Movement noise | • • • 0 0 |
| Attrition | • • • • |
| Corrosion resistance | • • • • • |

Dimensions



Structure & Mounting



ALPHA3477UOR200P63

EAN 4031582306194

Structure & Mounting

