

STYLEA

5925UJI075L51-10 DOM20 ALU

EAN 4031582311150

Swivel castor with wheel brake, housing made of Polyamide, with blind hole fitting. Wheel centre made of Polyamide, Tread: TENTEprene (thermoplastic rubber). Plain bearing



BETTER MOBILITY. BETTER LIFE.



Picture may differ from original product

Technical Data

| | |
|------------------------|----------------|
| Wheel diameter | 75 mm |
| Width of Tread | 8 mm |
| Castor width | 54 mm |
| Centre hole | 10 mm |
| Dome-Ø | 20 mm |
| Offset | 30 mm |
| Swivel Interference | 174 mm |
| Overall height | 77 mm |
| Temperature | - 20 / + 60 °C |
| Standard | EN 12528 |
| Weight | 0.15 kg |
| Swivel Radius | 87 mm |
| Hardness of tread | Shore A 87 |
| Load capacity | 50 kg |
| Load capacity (static) | 100 kg |

Structure & Mounting



Advantages at a glance

| | |
|----------------------|-----------|
| Roll performance | ● ● ● ○ ○ |
| Movement noise | ● ● ● ○ ○ |
| Attrition | ● ● ● ○ ○ |
| Corrosion resistance | ● ● ● ● ○ |