AGILA

7477PJO100P30-11

EAN 4031582350135

Swivel castor with total lock, tail end of castor, housing made of Stainless Steel, double ball bearing swivel head, wheel axle with nut, zinc-die-casted chrome-plated brake pedal, bolt hole. Wheel centre made of Polypropylene, Tread: TENTEprene (thermoplastic rubber), grey non-marking, plain bearing





Picture may differ from original product


Technical Data

| Wheel diameter | 100 mm |
|------------------------|----------------|
| Width of Tread | 32 mm |
| Castor width | 60 mm |
| Centre hole | 11 mm |
| Dome-Ø | 60 mm |
| Offset | 43.5 mm |
| Swivel Interference | 262 mm |
| Overall height | 135 mm |
| Temperature | - 20 / + 60 °C |
| Standard | EN 12530 |
| Weight | 0.669 kg |
| Swivel Radius | 131 mm |
| Hardness of tread | Shore A 87 |
| Load capacity | 80 kg |
| Load capacity (static) | 160 kg |

Advantages at a glance

| Roll performance | • • • 0 0 |
|----------------------|-----------|
| Movement noise | • • • 0 0 |
| Attrition | • • • 0 0 |
| Corrosion resistance | • • • • |

Dimensions



Structure & Mounting

